




## AIRLESS PAINT SPRAYERS



## HEAVY-DUTY PRESSURE WASHERS



## TEXTURE SPRAYERS



**TACKLE ANY JOB WITH CONFIDENCE!**

### Airless Tip Selection





From state-of-the-art features to our color-coded tip handles, we make spray tips easier to use and select. Plus, we provide the technology to give you durable, reliable accessories that delivers a consistent spray pattern for a variety of materials.

- Patented diffuser allows atomization at lower pressures, reducing tip wear and extending tip life
- Pinned handle resists twisting and breakage
- Reversible for easy cleaning
- Liquid-honed for long life and double-tested to ensure accurate spray pattern and flow rate
- Highest-quality carbide tip produces longer useable life
- Color-coded handles for easy identification

ASM's color-coded tip handle and corresponding tip selection guide make it simple to select the right orifice and fan pattern for your painting application. Follow the steps below for easy tip selection.

### Spray Tip Application Guide

- 1 - Identify the surface you will be spraying
- 2 - Choose your coating
- 3 - Determine your spray pattern width [spraying 12 in (30.5 cm) from the surface]
- 4 - Follow chart to tip number

-  Red — 200 Mesh, For Varnishes and Lacquers
-  Yellow — 100 Mesh, For Enamels and Stains
-  White — 50 Mesh, For Latex
-  Green — 30 Mesh, For Heavy-Bonded Paints

Tip handles are color-coded by orifice (tip hole) size for easy identification on the job site.

#### How to Determine Spray Tip Size:

EXAMPLE:  
 $\#5 = 1/2 \text{ Fan Width or } 2 \times 5 = 10 \text{ Inch Fan}$

**517**

#17 Orifice is diameter of opening in thousandths

Surface	Coating	Fan Width in Inches	Grey .009	Red .011	Orange .013	Yellow .015	Blue .017	Green .019	Purple .021	Brown .023	Black .025	Black .027	Black .029	Black .031	Black .035	Black .045	Black .061	Filter Mesh Color Code		
Wood Interiors,	Lacquer, Varnish, Shellac	2 in																		
		4 in	209	211																
		6 in	309	311																
		8 in	409	411	413															
		10 in	509	511	513															
	Alkyd Stain, Alkyd Enamel, Sanding Sealer	4 in		211	213															
		6 in		311	313															
		8 in		411	413	415														
		10 in					415	417	419											
		12 in					515	517	519											
Interior Walls, Ceilings, Drywall	Latex, Vinyl, Acrylic	2 in																		
		4 in		211	113	115														
		6 in			213	215														
		8 in			313	315														
		10 in				415	417	419												
Roof Overhangs	Primer, Enamel, Latex, Acrylic	2 in			113	115														
		4 in			213	215	217													
		6 in				315	317	319												
		8 in				415	417	419												
		10 in				515	517	519												
Masonry, Block, Stucco, Concrete	Vinyl, Oil Base, Alkyd	6 in																		
		8 in				415	417	419	421	423										
		10 in				515	517	519	521	523										
		12 in							621	623										
		16 in				615	617	619												
	Smooth Elastomeric	Latex, Acrylic	6 in																	
			8 in					419	421	423	425	427	429	431	435					
			10 in					519	521	523	525	527		531	535					
			12 in					619	621	623	625			631	635	645	661			
			16 in													835				
Wood Exteriors, Shingle Siding, Shiplap	Exterior Stain	6 in			315															
		8 in			415	417														
		10 in			515	517	519													
		12 in				617	619													
		16 in																		
Open Joists Ceiling Areas RIB Deck Ceilings	Mil White High Build	6 in			315	317	319	321												
		8 in				417	419	421												
		10 in				517	519	521												
		12 in					619	621												
		16 in				315	317													
Dry Fall	Dry Fall	6 in			415	417	419	421	423	425										
		8 in				517	519	521	523	525										
		10 in					621	623	625											
		12 in																		
		16 in																		

### Universal Reversible Spray Tips

- The Uni-Tip™ is universal with major brands, including Titan™, SprayTECH®, Graco® RAC® IV and RAC 5 and Airlessco®. Not compatible with Graco RAC X™, ASM Super-Zip™ or Zip-Tip™.
  - Best quality carbide tip means a superior spray pattern and a longer useable fan pattern life
  - The color-coded handle makes it easy to identify the tip size on the job
  - Each tip individually tested for consistent fan and orifice size
  - One-piece Uni-Tip seal means fewer parts on hand
  - Uni-Tip seal is compatible with the full range of paints and solvents
  - Pinned Handle resists twisting and breakage
  - Nib on handle for seal replacement
- Part # 69-XXX



### Striping Uni-Tip

- Specifically manufactured to provide crisp, clean edges
  - Available in all common striping tip sizes
- Part # 69xxxST

### Fine-Finish Uni-Tip

- All the features of the Uni-Tip Plus, double orifice gives greater break-up of fine-finish materials
  - Provides the finest atomization and a high-quality finish
  - Up to 85% transfer efficiency
- Part # 69-FFXXX

### Uni-Tip Hand-Tight Base/Guard (Tip not included)

- Aluminum won't rust
  - Virtually eliminates paint buildup and dripping
  - Easy no-tools assembly
  - Quickly change from horizontal to vertical spray pattern
- Part # 248200 "G" thread is 7/8" (22 mm)  
 Part # 249303 "F" thread is 11/16" (17 mm)



### Uni-Tip Seal

- Easily installs without tools!
- Part # 248228 (5-pack)



### Standard Uni-Tips (69-XXX)

Fan Width in Inches	Grey .009	Red .011	Orange .013	Yellow .015	Blue .017	Green .019	Purple .021	Brown .023	Black .025	Black .027	Black .029	Black .031	Black .035	Black .045	Black .061
2 in															
4 in	209	211	213	215	217	219	221								
6 in	309	311	313	315	317	319	321			327					
8 in	409	411	413	415	417	419	421	423	425	427	429	431	435		
10 in	509	511	513	515	517	519	521	523	525	527		531	535		
12 in	609		613	615	617	619	621	623	625			631	635	645	661
16 in														835	

### Striping Uni-Tips (69XXXST)


Fan Width in Inches	Yellow .015	Blue .017	Green .019	Purple .021	Black .027
4 in	215	217			
6 in	315	317	319	321	327
8 in		417			
10 in		517			
12 in	615	617			

### Fine Finish Uni-Tips (69-FFXXX)

Fan Width in Inches	Red .011	Orange .013	Yellow .015	Blue .017	Green .019
4 in	211	213	215		
6 in	311	313	315		
8 in	411	413	415		
10 in		513		517	
12 in					619

**Super-Zip Reversible Spray Tips**

- Liquid-honed and double-tested to ensure an accurate spray pattern
  - Patented diffusion chamber for superior atomization
  - Color-coded tip handles for easy selection
  - Reversible to quickly clear tip clogs
- Part # 59-xxx



**Striping Super-Zips**

- Specifically manufactured to provide crisp, clean edges
  - Available in all common striping tip sizes (213, 215, 315, 217, 317, 417, 219, 319, 419, 321, 421, 621, 323, 623, 625, 327, 627)
- Part # 59xxxST

**Fine-Finish Super-Zips**

- Double orifice gives greater break-up of fine-finish materials
  - Provides the finest atomization and a high-quality finish
  - Up to 85% transfer efficiency
- Part # 59FFXX-XXX



Fine-Finish Super Zips									
09	11	13	15	17	19	21	23	25	27
09	111	113	115	117	119	121	123	125	127
11	213	215	217	219	221	223	225	227	229
13	315	317	319	321	323	325	327	329	331
15	417	419	421	423	425	427	429	431	433
17	519	521	523	525	527	529	531	533	535
19	621	623	625	627	629	631	633	635	637

**Super-Zip Hand-Tight Base/Guard**

- Hand-Tight Base – no tools required!
  - Patented Cartridge Seal is compatible with all materials, will last through multiple tips and is spring-loaded for easy tip insertion and removal
  - Patented safety tab design locks for safe tip reversing when unlogging tip
  - Available to fit all makes of guns
- Part # 5901-F Fits "F" thread size - 11/16 in (17 mm)  
Part # 5901-G Fits "G" thread size - 7/8 in (22 mm)



**Super-Zip Cartridge Seals**


- Replace Cartridge Seals quickly, without tools
  - No loose gaskets
- Part # 5907 Hand-Tight Cartridge Seal



**Super-Zip Selection Guide**

FAN WIDTH IN INCHES	GREY	RED	ORANGE	YELLOW	BLUE	GREEN	PURPLE	BROWN	BLACK	BLACK	BLACK	REFERENCE	
	009 0.08	.011 0.12	.013 0.17	.015 0.23	.017 0.30	.019 0.36	.021 0.46	.023 0.55	.025 0.66	.027 0.77	.029 0.88		
2 in	•	111	113	115	117	119	121	•	•	•	•	COLOR ORIFICE SIZE GPM / FLOW	
4 in	209	211	213	215	217	219	221	•	•	•	•		
6 in	309	311	313	315	317	319	321	323	325	327	•		
8 in	409	411	413	415	417	419	421	423	425	427	429		
10 in	•	511	513	515	517	519	521	523	525	527	529		
12 in	•	611	613	615	617	619	621	623	625	627	629		
14 in	•	•	•	715	717	719	721	723	725	•	729		
16 in	•	•	•	815	817	819	821	823	•	827	829		
18 in	•	•	•	915	917	•	921	•	925	•	•		
2 in	•	•	•	•	•	•	•	•	•	•	•		FILTER Green 30 Mesh White 50 Mesh Yellow 100 Mesh Red 200 Mesh
4 in	•	•	•	•	•	•	•	•	•	•	•		
6 in	331	333	335	339	•	•	•	•	•	•	•		
8 in	431	433	435	439	441	443	445	447	449	451	453		
10 in	531	533	535	539	541	543	545	547	549	551	553		
12 in	631	633	635	639	641	643	645	647	649	651	653		
14 in	731	733	735	739	741	743	745	747	749	751	753		
16 in	831	833	835	839	•	•	•	•	•	•	•		
18 in	931	933	935	939	•	•	•	•	•	•	•		

REFERENCE  
 ----- COLOR  
 ----- ORIFICE SIZE  
 ----- GPM / FLOW



**Flat Tip Systems**

**Standard Flat Tips**

- Flat Tips are universal and fit all makes of Flat Tip Bases
- Part # 90-xxx



**Flat Tip Base/Guard**

- Flat Tip Bases are universal and are available to fit all makes of guns
  - Accommodates Flat Tip-n-Gasket (93-xxx) and Standard Flat Tips (90-xxx)
- Part # 420-F Fits "F" thread size - 11/16 in (17 mm)  
Part # 420-G Fits "G" thread size - 7/8 in (22 mm)
- Separate tip gasket available in tubes of eight (8)
- Part # 401-8



**Flat Tip Selection Guide**

FAN WIDTH IN INCHES	.007	.009	.011	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035	REFERENCE
	0.04	0.08	0.12	0.17	0.23	0.30	0.36	0.46	0.55	0.66	0.77	0.88	1.02	1.16	1.31	
2 in	•	109	111	113	115	•	119	121	•	•	•	•	•	•	•	ORIFICE SIZE GPM / FLOW
4 in	207	209	211	213	215	217	219	221	223	•	•	•	•	•	•	
6 in	307	309	311	313	315	317	319	321	323	•	•	•	•	•	•	
8 in	407	409	411	413	415	417	419	421	423	•	•	•	•	•	•	
10 in	•	509	511	513	515	517	519	521	523	•	•	•	•	•	•	
12 in	•	609	611	613	615	617	619	621	623	•	•	•	•	•	•	
14 in	•	•	•	•	715	717	719	721	723	•	•	•	•	•	•	
16 in	•	•	•	•	815	817	819	821	823	•	•	•	•	•	•	
18 in	•	•	•	•	•	917	•	921	•	•	•	•	•	•	•	

FAN WIDTH IN INCHES	.025	.027	.029	.031	.033	.035
	0.66	0.77	0.88	1.02	1.16	1.31
2 in	•	•	•	•	•	•
4 in	•	227	•	•	•	235
6 in	325	327	•	331	•	•
8 in	425	427	429	431	433	435
10 in	525	527	529	531	533	535
12 in	625	627	629	631	633	635
14 in	725	•	729	•	•	735
16 in	•	827	829	831	833	835
18 in	925	•	•	•	•	935

FAN WIDTH IN INCHES	.039	.043	.045	.051	.055
	1.62	1.98	2.16	2.81	3.17
2 in	•	•	•	•	•
4 in	•	•	•	•	•
6 in	•	•	•	•	•
8 in	439	•	•	451	•
10 in	•	543	•	•	•
12 in	•	•	645	•	655
14 in	•	•	•	•	•
16 in	•	•	•	•	•
18 in	•	•	•	•	•



THREAD SIZE ON DIFFUSER "F" = 11/16 "G" = 7/8

**Guns**

**500 Series Professional Airless Spray Gun**

The ASM 500 Contractor Gun is new and designed for durability, spraying performance and a long life (Includes 517 Uni-Tip and Guard)

- Lightweight gun with easy trigger pull
- Heavy-duty swivel allows easy gun movement
- Split handle for easy filter removal
- Available "G" thread only
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)
- Part # **289316** 2-Finger Gun with Uni-Tip
- Part # **288681** 4-Finger Gun with Uni-Tip
- Repair Kit # **288817**



**400 Series Professional Airless Spray Gun**

- Improved! Life of the 400 Series gun before repair is equal to or better than that of competitive guns (Includes 517 Uni-Tip and Guard)
- Heavy-duty swivel allows easy gun movement
- Anodized body resists corrosion
- Split handle for easy access to filter
- Available with "F" and "G" diffusers to match all systems
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)
- Part # **248240** 2-Finger Gun with Uni-Tip ("G" thread only)
- Part # **456-SF, 456-SG** 2-Finger Gun with Super-Zip
- Part # **248239** 4-Finger Gun with Uni-Tip ("G" thread only)
- Part # **451-SF, 451-SG** 4-Finger Gun with Super-Zip
- Repair Kit # **4427-F, 4427-G**



**300 Series Professional Airless Spray Gun**

- Improved! New needle design for reduced spitting and long life (Includes 517 Uni-Tip and Guard)
- Available with "F" and "G" diffusers to match all systems
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)
- Part # **248238** 2-Finger Gun with Uni-Tip ("G" thread only)
- Part # **356-SF, 356-SG** 2-Finger Gun with Super-Zip Tip
- Part # **248237** 4-Finger Gun with Uni-Tip ("G" thread only)
- Part # **351-SF, 351-SG** 4-Finger Gun with Super-Zip Tip
- Repair Kit # **3027-F, 3027-G**



**200 Series Airless Spray Gun**

- Easy-access in-handle paint filter reduces tip clogging and improves finish (Includes 515 Uni-Tip and Guard)
- Comfortable 4-Finger Trigger
- Ideal for small projects
- Maximum working pressure 3600 psi (24.8 MPa, 248 bar)
- Part # **251-U** 4-Finger Gun with Uni-Tip
- Part # **251-SG** 4-Finger Gun with Super-Zip Tip
- Not repairable



**Combo Gun**

- Well-balanced, lightweight, comfortable handle and trigger
- In-handle gun filter and internal trigger lock
- Add a Mini Pole or Maxi Pole for extra reach
- Part # **248241** with 517 Uni-Tip and Uni-Tip Hand-Tight Base ("G" thread only)
- Part # **6700-SF, 6700-SG** with 517 Super-Zip and Super-Zip Hand-Tight Base
- Repair Kit # **6727-F, 6727-G**



**Hose**

**Airless Hose**

- 3300 psi (22.7 MPa, 227 bar) rating
- Swivel couplers and spring guards on both ends
- Can be coupled with other airless hose
- Female fitting ends.
- Part # **HSE1450** 1/4 in (6.4 mm) x 50 ft (15 m)
- Part # **HSE3850** 3/8 in (9.5 mm) x 50 ft (15 m)
- Part # **245449** 1/4 in (6.4 mm) x 25 ft (7.5 m)



**Whip Hose**

- Whip Hoses add flexibility and reduce operator fatigue
- Part # **HSE3163** 3 ft (0.9 m) x 3/16 in (4.8 mm) (MXF)
- Part # **HSE3165** 5 ft (1.5 m) x 3/16 in (4.8 mm) (MXF)



**Gun Hose Kits**

- 500 Series Contractor Gun with Uni-Tip, Hand-Tight Base and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose ("G" thread only)
- Part # **256244** (4-Finger)
- Part # **256245** (2-Finger)
- 400 Series Professional Gun with Uni-Tip, Uni-Tip Hand-Tight Base and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose
- Part # **248249** ("G" thread only) (4-Finger)
- Part # **248250** ("G" thread only) (2-Finger)
- 400 Series Professional Gun with Super-Zip, Hand-Tight Base and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose
- Part # **451-SHF** ("F" thread), **451-SHG** ("G" thread) (4-Finger)
- Part # **456-SHF** ("F" thread), **456-SHG** ("G" thread) (2-Finger)
- 300 Series Contractor Gun with Super-Zip, Hand-Tight Base and 1/4 in (6.4 mm) x 50 ft (15 m) Airless Hose
- Part # **351-SHF** ("F" thread), Part # **351-SHG** ("G" thread) (4-Finger)
- Part # **356-SHF** ("F" thread), Part # **356-SHG** ("G" thread) (2-Finger)



**Gun and Hose Connectors**

- Part # **4410** 3/8 in (npt) x 3/8 in (npt) MBE
- Part # **4413** 1/4 in (npt) x 1/4 in (npt) Hex Nipple MBE
- Part # **4414** 1/4 in (npt) x 3/8 in (npt) MBE
- Part # **162485** 3/8 in (npt) x 3/8 in (npsm) MBE
- Part # **239663** 1/4 in (npt)(M) x 1/4 in (npsm)(F) Swivel

**Hose Cover**

- 4 mil poly protects your airless hose from paint and abrasion damage. Comes in 1000 ft roll with perforations every 50 ft
- Part # **865696** ASM Hose Cover Roll
- Part # **867610** ASM Hose Case of 6 Rolls



**Mini Poles**

- Durable stainless steel construction for rust resistance
- Hand-Tight system allows for easy attachment to gun, without tools

**3400 Series**

**With Uni-Tip Hand-Tight Base ("G" thread only)**

- 6 in (15.2 cm) Part # **248233**
- 12 in (30.5 cm) Part # **248234**
- 18 in (45.7 cm) Part # **248235**
- 24 in (61.0 cm) Part # **248236**

3400 Series Mini Pole



**With Super-Zip Hand-Tight Base**

- |                                       |                       |
|---------------------------------------|-----------------------|
| 6 in (15.2 cm) Part # <b>3406-SF</b>  | Part # <b>3406-SG</b> |
| 12 in (30.5 cm) Part # <b>3412-SF</b> | Part # <b>3412-SG</b> |
| 18 in (45.7 cm) Part # <b>3418-SF</b> | Part # <b>3418-SG</b> |
| 24 in (61.0 cm) Part # <b>3424-SF</b> | Part # <b>3424-SG</b> |

**With Flat Tip Base Wrench Tight**

- |                                      |                      |
|--------------------------------------|----------------------|
| 6 in (15.2 cm) Part # <b>2406-F</b>  | Part # <b>2406-G</b> |
| 12 in (30.5 cm) Part # <b>2412-F</b> | Part # <b>2412-G</b> |
| 18 in (45.7 cm) Part # <b>2418-F</b> | Part # <b>2418-G</b> |
| 24 in (61.0 cm) Part # <b>2424-F</b> | Part # <b>2424-G</b> |

**3500 Series\*(with Anglehead)**

**With Uni-Tip Hand-Tight Base ("G" thread only)**

- 6 in (15.2 cm) Part # **255258**
- 12 in (30.5 cm) Part # **255259**
- 18 in (45.7 cm) Part # **255260**
- 24 in (61.0 cm) Part # **255261**

3500 Series Mini Pole



**With Super-Zip Hand-Tight Base**

- |                                       |                       |
|---------------------------------------|-----------------------|
| 6 in (15.2 cm) Part # <b>3506-SF</b>  | Part # <b>3506-SG</b> |
| 12 in (30.5 cm) Part # <b>3512-SF</b> | Part # <b>3512-SG</b> |
| 18 in (45.7 cm) Part # <b>3518-SF</b> | Part # <b>3518-SG</b> |
| 24 in (61.0 cm) Part # <b>3524-SF</b> | Part # <b>3524-SG</b> |

**With Flat Tip Base Wrench Tight**

- |                                      |                      |
|--------------------------------------|----------------------|
| 6 in (15.2 cm) Part # <b>2506-F</b>  | Part # <b>2506-G</b> |
| 12 in (30.5 cm) Part # <b>2512-F</b> | Part # <b>2512-G</b> |
| 18 in (45.7 cm) Part # <b>2518-F</b> | Part # <b>2518-G</b> |
| 24 in (61.0 cm) Part # <b>2524-F</b> | Part # <b>2524-G</b> |

**Maxi Poles**

Hand-Tight Maxi Poles accept Hand-Tight adapters and an additional Maxi Pole or Mini Pole for 12 ft maximum length.

- Includes Anglehead™ to adjust spray angle
- Available in "F" and "G" thread sizes to fit all guns

**With Uni-Tip Hand-Tight Base ("G" thread only)**

- Part # **248242** 2 ft (60.9 cm)
- Part # **248243** 3 ft (91.4 cm)
- Part # **248244** 4 ft (121.9 cm)
- Part # **248245** 6 ft (182.9 cm)
- Part # **248246** 9 ft (274.2 cm)

**With Super-Zip Hand-Tight Base**

- Part # **7402-SF, 7402-SG** 2 ft (60.9 cm)
- Part # **7403-SF, 7403-SG** 3 ft (91.4 cm)
- Part # **7404-SF, 7404-SG** 4 ft (121.9 cm)
- Part # **7406-SF, 7406-SG** 6 ft (182.9 cm)
- Part # **7409-SF, 7409-SG** 9 ft (274.2 cm)

**With Flat Tip Base**

- Part # **7302-F, 7302-G** 2 ft (60.9 cm)
- Part # **7303-F, 7303-G** 3 ft (91.4 cm)
- Part # **7304-F, 7304-G** 4 ft (121.9 cm)
- Part # **7306-F, 7306-G** 6 ft (182.9 cm)
- Part # **7309-F, 7309-G** 9 ft (274.2 cm)

- Part # **3430-G, 3430-F** Connect two poles
- Part # **233951** Pole Gasket (1)

**AngleHead**

- In-line AngleHead Swivel provides accurate spraying at any height or angle
- Swivels to 90° (shown) for easy spraying of challenging areas
- Tip not included

- Part # **7506A** ("F" thread) no base included
- Part # **7506AG** ("G" thread) no base included
- Part # **248247** with Uni-Tip Hand-Tight Base ("G" thread only)
- Part # **7506-SF** with Super-Zip Hand-Tight Base
- Part # **7506-SG** with Super-Zip Hand-Tight Base
- Part # **7551-G** Pole to Gun Adapter, Hand-Tight
- Part # **7551-F** Pole to Gun Adapter, Hand-Tight
- Part # **87500G** With Flat Tip Guard, Wrench-Tight
- Part # **87500F** With Flat Tip Guard, Wrench-Tight
- Part # **7556-G** Pole Gun Adapter, Wrench-Tight
- Part # **7556-F** Pole Gun Adapter, Wrench-Tight



0° to 90° (90° Shown)

Maxi Pole



**Zip-Roll™ Pressure Roller**

The Zip-Roll pressure roller accessory attaches and is fed paint from your airless pump allowing you to use your system to roll in areas where spraying is not practical. Provides smooth, continuous delivery of paint to all types of surfaces. Just trigger gun to release paint to roller. Pressure rolling is 4 times faster than standard rolling!

- Extends reach – no need for a ladder
- Chrome-plated stainless steel frame provides rust resistance and eliminates streaking
- Hand-Tight system for easy assembly – no tools required

**Zip-Roll Pressure Roller**

(Includes Combo Gun)	3 ft	6 ft
Wrench-Tight with Flat Guard	Part # <b>970309(F)</b>	Part # <b>970609(F)</b>
Wrench-Tight with Flat Guard	Part # <b>970309(G)</b>	Part # <b>970609(G)</b>
Hand-Tight with Zip Guard	Part # <b>980309(F)</b>	Part # <b>980609(F)</b>
Hand-Tight with Zip Guard	Part # <b>980309(G)</b>	Part # <b>980609(G)</b>
Hand-Tight with Super Zip Guard	Part # <b>980309(SG)</b>	Part # <b>980609(SG)</b>
Hand-Tight with Super Zip Guard	Part # <b>980309(SF)</b>	Part # <b>980609(SF)</b>
Zip-Roll Frame only	Part # <b>244278</b>	



**45° Swivel Fitting Kit**

To be used between the gun and Heavy-Duty Extension for pressure rolling. ("G" to "G" thread)  
Kit Includes (**239531, 166969, 114049**)  
Part # **239531**



**Gun Filters – 2-Pack**

- Stainless Steel Mesh to eliminate rust
- 200 Series**  
Part # **248677** 60 Mesh & 100 Mesh (1 ea.)
- 300, 400, 500 Series and Combo Gun**  
Part # **4435-2** Extra Fine 200 Mesh Red for Varnishes and Lacquers  
Part # **4434-2** Fine 100 Mesh Yellow for Enamels and Stains  
Part # **4433-2** Medium 50 Mesh White for Latex Paints  
Part # **4436-2** Coarse 30 Mesh Green for Heavy-bodied Paints



**Paint Strainers**


Pre-filter your paint using Strainer Bags.  
Part # **865662** Suction Filter Cover – 12 Pack  
Part # **238769** Strainer Bags – 25 Pack



- Convenient Zip-Clip™ holds roller cover securely on frame and quickly releases for easy cleanup
- Few parts for quicker cleaning time

**Zip-Roll Pressure Roller**

Attaches to gun that comes with units. Includes: 45° "G" thread gun adapter, 24 in. (61 cm) extension, 9 in (23 cm) roller frame & 1/2 in (13 cm) nap cover  
Part # **287713**




**Zip-Roll Pressure Roller Covers**

High-quality, all-purpose Pressure Roller Covers, Available in a variety of Naps. (Must be ordered in multiples of 6)  
Part # **7721** Smooth Surfaces – 9 in x 3/8 in (23 cm x .95 cm)  
Part # **7722** Semi-Smooth Surfaces – 9 in x 1/2 in (23 cm x 1.27 cm)  
Part # **7723** Medium Surfaces – 9 in x 3/4 in (23 cm x 1.90 cm)  
Part # **7724** Rough Surfaces – 9 in x 1 1/4 in (23 cm x 3.18 cm)



**Quick Flush™**

- The only clean water flushing system
- Cuts Sprayer clean-up time in half!
- Connects to standard garden hose to backflush sprayer through gun
- Includes "F" Adapter to work with all brands of gun  
Part # **865681** (Spray gun not included)



**Gun Repair Kits**

- Includes Ball Valve Plunger, Assembly and Diffuser.  
Part # **288817** 500 Gun repair kit  
Part # **4427-F, 4427-G** 400 Series Gun  
Part # **3027-F, 3027-G** 300 Series gun  
Part # **6727-F, 6727-G** Combo Gun  
Note: 400 Series Gun Repair Kits may be used in 300 Series Guns.



**"F" to "G" Adapter**

- Converts 11/16 in (17 mm) "F" Thread to 7/8 in (22 mm) "G" Thread  
Part # **248248**



**ASM Professional Hopper Gun**

Sprays acoustics, drywall mud, waterproofing material, pool deck sealant, stucco, and most gravity-fed materials. Angled 1-1/2 gallon (5.7 L) hopper allows more material capacity for longer spraying before refills!

- Zip-Tex™ 650 Gun**  
Part # 288906 Gun only
- Zip-Tex 750, 900 and 1000**  
Part # 288905 Gun only  
Part # 246409 Gun including Hopper



**Spray Nozzles**

- Part # 234153 Beige, 4 mm — Fine Finish, Orange Peel  
White, 6 mm — Orange Peel, Fine Splatter  
Gray, 8 mm — Splatter, Small to Medium Knockdown  
Black, 12 mm — Acoustics, Large Knockdown, Popcorn

**Replacement Parts**

- Part # 234149 25 ft (7.6 m) Material/Air Hose (Zip-Tex 750, 900 & 1000)
- Part # 288622 20 ft Material/Air Hose Kit for Zip-Tex 650
- Part # 15C090 Viscosity Ball – All Machines
- Part # 234156 RotoFlex Replacement Pump Hose (Zip-Tex 750 & 1000 only) Recommended replacement after 2000-2500 gallons (7571-9463 L) of gypsum-based material
- Part # 288623 RotoFlex II Replacement Pump Hose (Zip-Tex 650 & 900 only)
- Part # 234159 Gun Repair Kit (All guns except 288906 Gun)
- Part # 258000 Gun Repair Kit for 288906 Gun
- Part # 234162 Material Hose Plug and Hopper Gun Attachment Plug
- Part # 234188 Hopper Clamp

**Fluids**

ASM fluids and protectants keep your equipment in top performing condition. ASM fluids are approved for use in all airless pumps.

**Pump Life™**

- Protects pump from corrosion and rust during short- and long-term storage
- Lubricates and cleans to help stop sticking valve seats
- Freeze proof to -30° F (-34° C)  
Part # 245650 (8 oz, 237 ml; 48 per case)  
245423 (32 oz, 946 ml; Available in multiples of 6)

**Packing Seal®**

- Prevents coating material from adhering to the pump's piston rod
- Prolongs pump packing life in all brands of piston pumps  
Part # 245427 (8 oz, 237 ml; Available in multiples of 6)  
Part # 245428 (32 oz, 946 ml; Available in multiples of 12)

**Hydraulic Fluid**

- Non-foaming formula
- Resists emulsifying and chemical breakdown  
Part # 245425 (32 oz, 946 ml; Available in multiples of 12)

**Starter Kit**

- For lubrication and protection  
Part # 245651 (8 oz, 237 ml; Pump Life) (4 oz, 119 ml; Packing Seal)

**STAY CLEAN™**

- Spray protectant for machine to prevent paint from sticking to it. Keeps your sprayer looking new for years!  
Part # 865705 (14 oz, 379 grams) case of 12 cans

**MagiCLEAN™**

- Safely removes paint from sprayers hose, tips and guns  
Part # 865657 (Starter kit with 3 gal. MagiCLEAN, strainer basket and residue tray)  
Part # 865656 Refill bottle for starter kit  
Part # 865655 Case of 12-8 oz jars for cleaning tips, guards and gun filters

**Pump Conditioner**

- Should be used on piston pumps between uses to prevent paint from drying on the piston & causing packing wear  
Part # 865712 Display of 48 - 1 oz bottles  
Part # 865714 (1 Quart; .951) bottle – case of 12  
Part # 865715 (1 Gallon; 3.78 l) bottle – case of 4  
Case quantity: 12 on quarts, 4 on gallons

PRESSURE WASHER ACCESSORIES

**Standard Nozzles (2525)(2730)**

- Part # 244768 - Includes: 0°, 15°, 25°, 40°
- Part # 805634 - Includes: Chemical Injector Nozzle
- Part # 805535 - 0° Red
- Part # 805536 - 15° Yellow
- Part # 805537 - 25° Green
- Part # 805538 - 40° White



**Standard Nozzle (3030)**

- Part # 244769 - Includes: 0°, 15°, 25°, 40°
- Part # 805634 - Includes: Chemical Injector Nozzle
- Part # 805539 - 0° Red
- Part # 805540 - 15° Yellow
- Part # 805541 - 25° Green
- Part # 805542 - 40° White



**Rotating Nozzle**

- Part # 198012
- Oscillating Nozzle** (Not Shown)
- Part # 198013

**High Pressure Non-Marking Hose**

- 3/8 in x 50 ft (10 mm x 15 m), 3000 psi (21.0 MPa, 210 bar)  
Part # 245416 for 2730/3030
- 3/8 in x 30 ft (10 mm x 8 m), 3000 psi (21.0 MPa, 210 bar)  
Part # 118125 for 2525



**Guns**

- Part # 244784 Gun with vented composite wand handle and quick-connect fittings, 5000 psi (344 bar, 34.4 MPa) max. working pressure  
Part # 246674 for use with 2525 only Gun only  
Part # 118124 Gun Extension for 2525





A DIVISION OF GRACO®

### **ASM CUSTOMER SERVICE**

20500 David Koch Ave.  
Rogers, MN 55374  
Phone: 800-854-4025  
Fax: 800-228-5104

### **WARRANTY**

ASM warrants its products to be free of defects in material and workmanship for one year. See operation manual for complete warranty information.

### **ASM AUTHORIZED SERVICE AGENCIES**

Call 1-800-854-4025 or see our website for the nearest ASM Authorized Service Agency.

**VISIT US ON THE WEB FOR PROMOTIONS,  
PRODUCT UPDATES, MANUALS, SERVICE CENTERS  
AND GENERAL INFORMATION.**

**[www.asmcompany.com](http://www.asmcompany.com)**



©2010 ASM Company. Form No. 341524 Rev. A 12/10 Printed in U.S.A.  
All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

**TACKLE ANY JOB WITH CONFIDENCE!**